| DECLARATION OF PERFORMANCE (DoP) | | | | |
|--|--|--|--|--|
| No. 10036-SFR-2019/01/01 | | | | |
| 1. Unique identification code of the product type: | | | | |
| Halton Sec Fit Rectangular (SFR) | | | | |
| Smoke control damper, fire resistance class: E ₆₀₀ 90 (v _{ed} -i↔o) S1000C ₃₀₀ AAsingle | | | | |
| 2. Intended use: | | | | |
| Smoke control dampers that are to be used in smoke control systems in single compartment applications at temperatures up 600°C. | | | | |
| 3. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant Article 11(5): Halton Oy Haltonintie 1-3 47400 Kausala FINLAND Tel. +358 (0)20792 200 Code: Hal 26724 | | | | |
| 4. System of AVCP: System 1 See Regulation (EU) No. 305/2011 (CPR) Annex V, 1.2. | | | | |
| 5. Harmonised standard: | | | | |
| EN 12101-8:2011 | | | | |
| 6. Notified body: | | | | |
| Notified body No. 1391 PAVUS, a.s. Prosecká 412/74, 19000 Praha 9-Prosek CE certificate of Constancy of Performance No: 1391-CPR-2018/0209 | | | | |
| | | | | |

| Essential characteristics | Requirements of EN 12101-8 | Findings ¹⁾ | Conformity Assessment | |
|--|-------------------------------|--|--------------------------|--|
| Nominal activation conditions/sensitivity | 4.2.1.3 | Comply with EN 12101-8, 4.2.1.3 | Conforms | |
| Response delay (response time) | 4.2.1.4 | < 60 s, according to EN 12101-8, 4.2.1.4 | Conforms | |
| Operational reliability | 4.3.2.2 | C 10 000 | Conforms | |
| Fire resistance | | | | |
| - Integrity (E) | 4.1.1, a), 4.3.1 | E < 360 m³ / (h.m²) | Conforms | |
| - Insulation (EI) | - | - 2) | NPD | |
| - Smoke leakage (ES) | 4.1.1, c), 4.3.1 | S < 200 m³ / (h.m²) | Conforms | |
| - Mechanical stability (under E) | 4.1.1, d) | E – requirements fulfilled | Conforms | |
| - Maintenance of the cross section (under E) | 4.1.1, e) | E – requirements fulfilled | Conforms | |
| - High operational temperature | 4.1.1, f), 4.3.1 | - | NPD | |
| Durability | | | | |
| - of response delay | 4.3.2.1 | < 60 s | Conforms | |
| - of operational reliability | 4.3.2.2 | C 300, response time < 120 s | Conforms | |

7. Declared performance/s of Halton Sec Fit Rectangular (SFR)

¹⁾ Detailed technical parameters, fire classification and conditions of final classification according to EN 13501-4:2016 are stated in the certification report no: P-1391-CPR-2018/0209 of 29th October 2018.

²⁾ For single compartment smoke control dampers it is not required/declared.



8. The performance of the product identified in point 1 is in conformity with the set of declared performance/s.

This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 (CPR), under the sole responsibility of the manufacturer identified in point 3.

Copy of Declaration of Perfomance (DoP) for Halton Sec Fit Rectangular (SFR) is available on website:

www.halton.com

Signed for and on behalf of the manufacturer by:

Raimo Parkkila - Manager, System and Product Development

Kausala, 1st of January 2019

Rames Portleta

